

JF-330 PROFILE GRINDER (1:1)



JF-330 Micro-adjustment for wheel head angle



- Work table back-front, left-right are moved with $\varnothing 9$, $\varnothing 6$ mm linear bearing cross roller rail sets, accuracy ± 0.005 mm, grinding length is up to 250mm.
- Grinding wheel head is micro-adjustable and accurate, 3HP variable speed motor is powerful for grinding.
- Knife edge angle is adjusted by dovetail arc groove, grinding center is never changed no matter what the angle is. Easy and efficient to operate.
- Water splash guard and coolant tank are stainless steel.

JC-312 PROFILE GRINDER (1:1)



JC-312 Wheel Dresser



- Work table back-front, left-right are moved with $\varnothing 9$, $\varnothing 6$ mm linear bearing cross roller rail sets, accuracy ± 0.005 mm, grinding length is up to 300mm.
- Water splash guard and coolant tank are stainless steel.
- Side clearance angle : 5° , 10° and 15°
- Back relief angle : 10° to 30°



JF-330 Standard attachments: Cutter spindles of $\varnothing 1''$, $\varnothing 40$ mm, $\varnothing 50$ mm each



JC-312, JF-330. Work table with linear bearing cross roller rail sets



JC-312 Center-gauge



JC-312 Standard attachments: Cutter spindles of $\varnothing 1''$, $\varnothing 40$ mm, $\varnothing 50$ mm each